

Material Safety Data Sheet

Dyno Nobel Inc.

2650 Decker Lake Boulevard, Suite 300
Salt Lake City, Utah 84119
Phone: 801-364-4800 Fax: 801-321-6703
E-Mail: dna.hse@am.dynonobel.com

FOR 24 HOUR **EMERGENCY, CALL** **CHEMTREC (USA) 800-424-9300**
CANUTEC (CANADA) 613-996-6666

MSDS # 1009
Date 01/31/05

Supersedes
MSDS # 1009 06/01/04

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s): ANFO
DYNOMIX™, DYNOMIX™ (U.G.)
DYNOMIX™ WR
DYNOMIX™ HD

Product Class: ANFO, Bulk or Packaged

Product Appearance & Odor: Pale, oil-covered prills with fuel oil odor.

Hazard Shipping Description (U.S. DOT and Canada TDGR)

For ANFO, DYNOMIX™, DYNOMIX™ (U.G.) Ammonium nitrate-fuel oil mixture 1.5D NA0331 II
Explosive blasting, type B 1.5D UN0331 II

Note: Either description is acceptable, but if already packaged, refer to packaging for which description to use.

For DYNOMIX™ WR: Explosive blasting, type B 1.5D UN0331 II
For DYNOMIX™ HD (Canada only): Explosive blasting, type B 1.1D UN0082 II

NFPA Hazard Classification: Not Available (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredients:</u>	<u>CAS#</u>	<u>% (Range)</u>	<u>Occupational Exposure Limits</u>	
			<u>ACGIH TLV-TWA</u>	<u>OSHA PEL-TWA</u>
Ammonium Nitrate	6484-52-2	92-95	None ¹	None ²
Fuel Oil	68476-34-6	4-7	100 ppm	None
Guar Gum*	9000-30-0	0-3	None ¹	None ²

¹ Use limit for particulates not otherwise regulated (PNOR): Total dust, 15 mg/m³; respirable fraction, 5 mg/m³.

² Use limit for particulates not otherwise classified (PNOC): Inhalable particulate, 10 mg/m³; respirable part., 3 mg/m³.

* **DYNOMIX™ WR is the only product containing guar gum.**

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

Material Safety Data Sheet

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable
Vapor Density: > 1
Percent Volatile by Volume: < 8 (Fuel oil)

Evaporation Rate (Butyl Acetate = 1): < 1

Vapor Pressure: <5 mm Hg @ 75° F
Density: 0.8 to 1.0 g/cc bulk density
Solubility in Water: Ammonium Nitrate component completely soluble

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: >120° F (49°C) **Flammable Limits:** Not Available
Extinguishing Media: (See Special Fire Fighting Procedures section.)
Special Fire Fighting Procedures: Do not attempt to fight fires involving explosive materials. Evacuate all personnel to a predetermined safe location, no less than 2,500 feet in all directions.
Unusual Fire and Explosion Hazards: Can explode or detonate under fire conditions. Burning material may produce toxic vapors.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

Eyes: May cause irritation, redness and tearing.
Skin: Prolonged contact may cause irritation.
Ingestion: Large amounts may be harmful if swallowed.
Inhalation: May cause dizziness, nausea or intestinal upset.
Systemic or Other Effects: None known.

Emergency and First Aid Procedures

Eyes: Irrigate with running water for at least 15 minutes. If irritation persists, seek medical attention.
Skin: Wash with soap and water.
Ingestion: Seek medical attention.
Inhalation: Remove to fresh air.
Special Considerations: None.

SECTION VI - REACTIVITY DATA

Stability: Stable under normal conditions. May explode when subjected to fire, supersonic shock or high-energy projectile impact, especially when confined or in large quantities.
Conditions to Avoid: Keep away from heat, flame, ignition sources and strong shock.
Materials to Avoid (Incompatibility): Corrosives (strong acids and strong bases or alkalis).
Hazardous Decomposition Products: Carbon Monoxide (CO) and Nitrogen Oxides (NO_x)
Hazardous Polymerization: Will not occur.

Material Safety Data Sheet

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: In case of fire evacuate area not less than 2,500 feet in all directions. Protect from all ignition sources. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If no fire danger is present, and product is undamaged and/or uncontaminated, repackage product in original packaging or other clean DOT approved container. Ensure that a complete account of product has been made and is verified. Follow applicable Federal; State and local spill reporting requirements.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Not required for normal handling. Forced ventilation may be necessary where natural ventilation is limited.

Respiratory Protection: None normally required. In a dusty environment, or in hot, enclosed areas, respiratory protection may be needed.

Protective Clothing: Gloves and work clothing that reduce skin contact are suggested.

Eye Protection: Safety glasses are recommended.

Other Precautions Required: None.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated locations. Store in compliance with Federal, State, and local regulations. Keep away from heat, flame, ignition sources and strong shock.

Precautions to be taken during use: Avoid breathing the fumes from detonation of explosives. Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library publications.

SECTION X - SPECIAL INFORMATION

The reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372 may become applicable if the physical state of this product is changed to an aqueous solution. If an aqueous solution of this product is manufactured, processed, or otherwise used, the nitrate compounds category and ammonia listing of the previously referenced regulation should be reviewed.

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.