


FireLine™ 21/100 PETN PLASTIC

Oil Field Detonating Cord




Product Description

FIRELINE 21/100 PETN PLASTIC is designed for use in “backoff” applications in relatively mild down hole conditions for a short time period (see graph below).

Temperature Range

The temperatures listed are maximum values. DO NOT EXCEED.



Technical Information



Properties

MSDS
#1121

Explosive Core Load	21 g/m (100 gr/ft) nominal 17 g/m (80 gr/ft) minimum
Detonation Velocity	6800 m/s (22,304 ft/s) nominal 6400 m/s (20,992 ft/s) minimum
Shrinkage	Not Tested
Jacket Thickness	0.20 mm (0.008 in) minimum
Dimensions	5.97 mm (0.235 in) nominal ± 0.025 mm (0.010 in)
Lap Joint Sensitive	Yes
Product Code	A379052
Cord Components	PETN explosive core (white) Poly-textile braid (white) Polyethylene jacket (white)

- **Temperature resistance** is based upon the manufacturer’s laboratory tests in air, at ambient pressure only.
- **Shrinkage** is defined as the overall decrease in length.
- **Velocity** was tested unconfined, at ambient pressure, and after “cool down.”

Hazardous Shipping Description

Cord, Detonating, 1.1D UN 0065 II EX 1992020035



S-17-03-01-06

See Product Disclaimer on page 2.

FireLine™

21/100 PETN PLASTIC

Technical Information



Transportation, Storage and Handling

- For maximum shelf-life, detonating cord must be stored in cool, dry, well-ventilated magazines. Explosives inventory should be rotated. Use older inventory first. Recommended shelf life, under proper storage conditions, is ten (10) years from date of manufacture.
- FIRELINE detonating cords must be transported, stored, handled and used in conformity with all federal, state, provincial and local laws and regulations.

Application Recommendations

- **This product is not recommended for exposure to well bore fluids.**
- **ALWAYS** cut FIRELINE 21/100 PETN PLASTIC detonating cord with a sharp knife.
- **NEVER** attempt to cut FIRELINE 21/100 PETN PLASTIC detonating cord with a blow from a sharp or blunt object, such as an axe, pipe wrench, or rock.
- **NEVER** saw FIRELINE 21/100 PETN PLASTIC detonating cord; it may explode and kill or injure.
- **NEVER** cut detonating cord with devices that produce metal-to-metal contact, such as scissors, wire cutters, crimpers or similar instruments.

Packaging

Package	Gross Weight		Net Weight		Explosive Weight		Spools/Case	Length/Spool*	
	kg	lbs	kg	lbs	kg	lbs		m	ft
Fiberboard box	10.9	24	10.4	23	6.5	14.3	2	152	500

- Weights represent nominal values.

* ±2%; 152m spools may contain as many as 3 pieces, totally 152 m, with a minimum splice/piece length of 8 m (25 ft).

Case Dimensions

28 x 28 x 40 cm 11 x 11 x 15 ¾ in

Product Disclaimer Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.



dnx
 2650 Decker Lake Boulevard, Suite 300, Salt Lake City, Utah 84119 USA
 Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com