

Material Safety Data Sheet

Dyno Nobel Inc.2795 East Cottonwood Parkway, Suite 500
Salt Lake City, Utah 84121

Phone: 801-364-4800 Fax: 801-321-6703

E-Mail: dna.hse@am.dynonobel.com**FOR 24 HOUR EMERGENCY, CALL** CHEMTREC (USA) 800-424-9300
CANUTEC (CANADA) 613-996-6666**MSDS # 1122****Date 09/16/10**

Supersedes

MSDS # 1122 01/22/09

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s): NONEL[®] MS
NONEL[®] MS ARCTIC
NONEL[®] LP
NONEL[®] SL
NONEL[®] TD
NONEL[®] MS CONNECTOR
NONEL[®] TWINPLEX[™]
NONEL[®] STARTER

NONEL[®] EZ DET[®]
NONEL[®] EZTL[™]
NONEL[®] EZ DRIFTER[®]

Product Class: NONEL[®] Non-electric Delay Detonators**Product Appearance & Odor:** Aluminum cylindrical shell with varying length and diameter of attached colored plastic tubing. The detonator may be enclosed in a plastic housing, and an assembly may contain two detonators. Odorless.**DOT Hazard Shipping Description:** UN0029 Detonators, non-electric 1.1B II
-or- UN0360 Detonator assemblies, non-electric 1.1B II
-or- UN0361 Detonator assemblies, non-electric 1.4B II**NFPA Hazard Classification:** Not Applicable (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

Occupational Exposure Limits

Ingredients	CAS#	OSHA PEL-TWA	ACGIH TLV-TWA
Pentaerythritol Tetranitrate (PETN)	78-11-5	None ¹	None ²
Lead Azide	13424-46-9	0.05 mg (Pb)/m ³	0.05 mg (Pb)/m ³
Lead	7439-92-1	0.05 mg (Pb)/m ³	0.05 mg (Pb)/m ³
Silicon	7440-21-3	15 mg / m ³ (total dust) 5 mg / m ³ (respirable fraction)	10 mg / m ³
Selenium	7782-49-2	0.2 mg/m ³	0.2 mg/m ³
Red Lead (Lead tetroxide)	1314-41-6	0.05 mg (Pb)/m ³	0.05 mg (Pb)/m ³
Titanium dioxide	13463-67-7	15 mg/m ³	10 mg/m ³
Barium Chromate	10294-40-3	1 mg (CrO ₃)/10m ³ (ceiling)	0.01 mg (Cr)/m ³
Lead Chromate	7758-97-6	0.5 mg (Ba)/m ³ 0.05 mg (Pb)/m ³ 1 mg (CrO ₃)/10m ³ (ceiling)	0.5 mg (Ba)/m ³ 0.15 mg (Pb)/m ³ 0.012 mg (Cr)/m ³
Barium Sulfate	7727-43-7	0.5 mg (Ba)/m ³	10 mg/m ³
Potassium Perchlorate ³	7778-74-7	None ¹	None ²
Silica (crystalline)	61790-53-2	See Note Below	0.05 mg/m ³ (resp frac)

Material Safety Data Sheet

Molybdenum	7439-98-7	None ¹	None ²
Tungsten	7440-33-7	None ¹	5 mg/m ³ (TWA) 10 mg/m ³ (STEL)
Aluminum	7429-90-5	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	5 mg/m ³
Antimony	7440-36-0	0.5 mg/m ³	0.5 mg/m ³
Cyclotetramethylene Tetranitramine (HMX)	2691-41-0	None ¹	None ²

¹ Use limit for particulates not otherwise regulated (PNOR): Total dust, 15 mg/m³; respirable fraction, 5 mg/m³.

² Use limit for particulates not otherwise classified (PNOC): Inhalable particulate, 10 mg/m³; respirable part., 3 mg/m³.

Note: The OSHA PEL for crystalline silica is calculated as follows:

Quartz, respirable: $10 \text{ mg/m}^3 \times \% \text{ SiO}_2 + 2$ Quartz, total dust: $30 \text{ mg/m}^3 \times \% \text{ SiO}_2 + 2$

³ Not all delay periods contain perchlorate. Those that do contain between from about 4 to a maximum of about 60 mg perchlorate per detonator.

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable

Vapor Density: Not Applicable

Percent Volatile by Volume: Not Applicable

Evaporation Rate (Butyl Acetate = 1): Not Applicable

Vapor Pressure: Not Applicable

Density: Not Applicable

Solubility in Water: Not Applicable

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable

Flammable Limits: Not Applicable

Extinguishing Media: (See Special Fire Fighting Procedures section.)

Special Fire Fighting Procedures: Do not attempt to fight fires involving explosive materials. Evacuate all personnel to a predetermined safe, distant location. Allow fire to burn unless it can be fought remotely or with fixed extinguishing systems (sprinklers).

Unusual Fire and Explosion Hazards: Can explode or detonate under fire conditions. Burning material may produce toxic vapors.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

This is a packaged product that will not result in exposure to the explosive material under normal conditions of use. Exposure concerns are primarily with post-detonation reaction products, particularly heavy metal compounds.

Eyes: No exposure to chemical hazards anticipated with normal handling procedures. Particulates in the eye may cause irritation, redness, swelling, itching, pain and tearing.

Skin: No exposure to chemical hazards anticipated with normal handling procedures. Exposure to post-detonation reaction products may cause irritation.

Ingestion: No exposure to chemical hazards anticipated with normal handling procedures. Post-detonation reaction product residue is toxic by ingestion. Symptoms may include gastroenteritis with abdominal pain, nausea, vomiting and diarrhea. See systemic effects below.

Material Safety Data Sheet

Inhalation: Not a likely route of exposure. See systemic effects below.

Systemic or Other Effects: None anticipated with normal handling procedures. Repeated inhalation or ingestion of post-detonation reaction products may lead to systemic effects such as respiratory tract irritation, ringing of the ears, dizziness, elevated blood pressure, blurred vision and tremors. Heavy metal (lead) poisoning can occur.

Carcinogenicity: ACGIH classifies Lead as a "Suspected Human Carcinogen" and insoluble Chromium VI as "Confirmed Human Carcinogen". NTP, OSHA, and IARC consider components contained in this detonator carcinogenic.

Perchlorate: Perchlorate can potentially inhibit iodide uptake by the thyroid and result in a decrease in thyroid hormone. The National Academy of Sciences (NAS) has reviewed the toxicity of perchlorate and has concluded that even the most sensitive populations could ingest up to 0.7 microgram perchlorate per kilogram of body weight per day without adversely affecting health. The USEPA must establish a maximum contaminant level (MCL) for perchlorate in drinking water by 2007, and this study by NAS may result in a recommendation of about 20 ppb for the MCL.

Emergency and First Aid Procedures

Eyes: Irrigate with running water for at least fifteen minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water.

Ingestion: Seek medical attention.

Inhalation: Not applicable.

Special Considerations: None

SECTION VI - REACTIVITY DATA

Stability: Stable under normal conditions, may explode when subjected to fire, supersonic shock or high-energy projectile impact.

Conditions to Avoid: Keep away from heat, flame, ignition sources, impact, friction, electrostatic discharge and strong shock. Do not attempt to disassemble.

Materials to Avoid (Incompatibility): Corrosives (acids and bases or alkalis).

Hazardous Decomposition Products: Carbon Monoxide (CO), Nitrous Oxides (NO_x), Sulfides, Chromates, Lead (Pb), Antimony (Sb) and various oxides and complex oxides of metals.

Hazardous Polymerization: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Protect from all ignition sources. In case of fire evacuate all personnel to a safe distant area and allow to burn or fight fire remotely. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If no fire danger is present, and product is undamaged and/or uncontaminated, repackage product in original packaging or other clean DOT approved container. Ensure that a complete account of product has been made and is verified. If loose explosive powder is spilled, such as from a broken detonator, only properly qualified and authorized personnel should be involved with handling and clean-up activities. Spilled explosive powder is extremely sensitive to initiation and may detonate. Follow applicable Federal, State, and local spill reporting requirements.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

Material Safety Data Sheet

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: None required for normal handling. Provide enhanced ventilation after use if in underground mines or other enclosed areas.

Respiratory Protection: None required for normal handling.

Protective Clothing: Cotton gloves are recommended.

Eye Protection: Safety glasses are recommended.

Other Precautions Required: None.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated location. Store in compliance with Federal, State, and local regulations. Only properly qualified and authorized personnel should handle and use explosives. Keep away from heat, flame, ignition sources, impact, friction, electrostatic discharge and strong shock.

Precautions to be taken during use: Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death. Avoid breathing the fumes or gases from detonation of explosives. Detonation in confined or unventilated areas may result in exposure to hazardous fumes or oxygen deficiency.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library Publications.

Material Safety Data Sheet

SECTION X - SPECIAL INFORMATION

These products contain the following substances that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Max. lbs/1000 units</u>
Lead	7439-92-1	39.4
	(Use Toxic Chemical Category Code)	
Lead Compounds	N420	2.0
Barium Compounds	N040	1.8
Chromium Compounds	N090	1.9

Range* of Section 313 Chemicals in each product

Product	lb Pb per 1000 detonators	lb Pb compounds per 1000 detonators	lb Ba compounds per 1000 detonators	lb Cr compounds per 1000 detonators
NONEL [®] MS	0 - 27	0.3 - 1.5	0 - 0.9	0 - 0.9
NONEL [®] LP	0 - 30	0.3 - 2.0	0 - 1.8	0 - 1.9
NONEL [®] SL	7 - 27	0.3 - 1.5	0	0
NONEL [®] TD	0 - 18	0.3 - 0.7	0	0
NONEL [®] MS Connector	5 - 16	0.3 - 0.4	0	0
NONEL [®] TWINPLEX [™]	5 - 15	0.3 - 0.7	0	0
NONEL [®] STARTER	0	0.3	0	0
NONEL [®] EZ DET [®]	22 - 36	2.0	0	0
NONEL [®] EZTL [™]	5 - 15	0.5 - 0.7	0	0
NONEL [®] EZ DRIFTER	39.4	1.3	1.2	1.3

* The exact quantity and weight percent of Section 313 Chemicals in each delay period and tubing length for each product is available upon request.

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.