


# FireLine® 8/40 RDX LS RIBBON

## Oil Field Detonating Cord




### Product Description

FIRELINE 8/40 RDX LS RIBBON is specially processed ribbon detonating cord using “shrinkage resistant” construction components. Its recommended application is “RTG” (retrievable tubing gun) perforating systems (1-11/16”, 2-1/8”, 2-3/4”) and should be employed within the normal RDX operating range (see graph below). Ribbon cord utilizes minimum carrier I.D. space allowing for an application of a larger designed shape charge.

### Temperature Range

The temperatures listed are maximum values. **DO NOT EXCEED.**



## Technical Information



## Properties

MSDS  
#1121

<b>Explosive Coreload</b>	8.6 g/m (40 gr/ft) nominal 7.2 g/m (34 gr/ft) minimum
<b>Detonation Velocity</b>	7800 m/s (24,600 ft/s) nominal 7100 m/s (22,960 ft/s) minimum
<b>Shrinkage</b>	1% maximum @ 163°C (325°F) in 24 hrs
<b>Jacket Thickness</b>	0.20 mm (0.008 in) nominal
<b>Dimensions</b>	5.53 mm (0.218 in) width maximum 3.30 mm (0.130 in) height maximum
<b>Lap Joint Sensitive</b>	Yes
<b>Product Code</b>	A538010
<b>Cord Components</b>	RDX explosive core (dyed pink) Shrink resistant braid (yellow/gold) Nylon jacket (black)

- **Temperature resistance** is based upon the manufacturer’s laboratory tests in air, at ambient pressure only.
- **Shrinkage** is defined as the overall decrease in length.
- **Velocity** was tested unconfined, at ambient pressure, and after “cool down.”

### Hazardous Shipping Description

Cord, Detonating, 1.1D, UN 0065 II EX 1992020035

**Alternative packaging: FIREPAK® 1.4S air cargo shipping containers**

Product Code A538017

Articles, Explosive 1.4S UN 0349 II EX 1999010231



S-23-07-31-07

See Product Disclaimer on page 2.

# FireLine® 8/40 RDX LS RIBBON

## Technical Information



### Transportation, Storage and Handling

- For maximum shelf-life, detonating cord must be stored in cool, dry, well-ventilated magazines. Explosives inventory should be rotated. Use older inventory first. Recommended shelf life, under proper storage conditions, is ten (10) years from date of manufacture.
- FIRELINE 8/40 RDX LS RIBBON detonating cords must be transported, stored, handled and used in conformity with all federal, state, provincial and local laws and regulations.

### Application Recommendations

- **This product is not recommended for exposure to well bore fluids.**
- **ALWAYS** cut FIRELINE 8/40 RDX LS RIBBON detonating cord with a sharp knife.
- **NEVER** attempt to cut FIRELINE 8/40 RDX LS RIBBON detonating cord with a blow from a sharp or blunt object, such as an axe, pipe wrench, or rock.
- **NEVER** saw FIRELINE 8/40 RDX LS RIBBON detonating cord; it may explode and kill or injure.
- **NEVER** cut detonating cord with devices that produce metal-to-metal contact, such as scissors, wire cutters, crimpers or similar instruments.

### Packaging

Package	Gross Weight		Net Weight		Explosive Weight		Spools/ Case	Length/ Spool*	
	kg	lbs	kg	lbs	kg	lbs		m	ft
Fiberboard box	3.3	7.3	3.1	6.8	1.3	2.9	1	152	500

• Weights represent nominal values.

\*  $\pm 2\%$ ; 152m spools may contain as many as 3 pieces, totally 152 m, with a minimum splice/piece length of 8 m (25 ft).

CE0519 ENB/C/024/06

### Case Dimensions

26 x 26 x 14 cm    10 ¼ x 10 ¼ x 5 ½ in

**Product Disclaimer** Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.



dnx

2650 Decker Lake Boulevard, Suite 300, Salt Lake City, Utah 84119 USA  
Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com