

UREA SOLUTION

Technical
Information



Aqueous NO_x Abatement Solution - 32.5% & 40%

Product Description

The UREA SOLUTION is created by dissolution of the pure amide directly into clean condensate so there are no ions of any metals present. The lowest salt-out temperature possible for UREA solution is 12°F at a 32.5% UREA concentration. The 40% UREA solution has a salt-out temperature of 32°F.

Application Recommendations

- UREA solutions are marketed as ultra clean liquid fuel for catalytic abatement of nitrogen oxide emissions.
- The decomposition of UREA solution into ammonia, carbon dioxide and steam provides a safe way to produce the ammonia fuel source. There is no need to have containers of compressed liquid ammonia in remote locations that are difficult to secure.
- Consult your Dyno Nobel representative for additional information.

Transportation, Storage and Handling

- The transport of UREA solution does not require a DOT placard.
- UREA solution will decompose into ammonia, carbon dioxide at 275 °F.
- **ALWAYS** thoroughly wash vessels containing UREA solution before attempting repairs requiring welding.

Hazardous Shipping Description

- There are no DOT restrictions, other than weight, to transport UREA solutions.
- Consult MSDS #1135 for more specific and comprehensive information about chemical hazards.

Properties

MSDS
#1135

UREA % by weight	32.0 to 33.0	39.5 to 40.5
Water % by weight maximum	67.0 to 68.0	59.5 to 60.5
Biuret % by weight maximum	0.3	0.3
Free Ammonia % by weight maximum	0.1	0.1
Carbonate (as CO ₂) % by weight	0.1	0.1
pH	8.0 – 10.0	8.0 – 10.0
Salt-out Temperature (open vessel)	~12°F	~32°F
Storage Temperature	40 to 80°F	40 to 80°F
Weight @ 68°F	9.1 lbs/gallon	9.4 lbs/gallon
Calcium maximum	0.5 ppm	0.5 ppm
Chromium maximum	0.5 ppm	0.5 ppm
Copper maximum	0.5 ppm	0.5 ppm
Iron maximum	0.5 ppm	0.5 ppm
Magnesium maximum	0.5 ppm	0.5 ppm
Nickel maximum	0.5 ppm	0.5 ppm
Phosphorus maximum	0.5 ppm	0.5 ppm
Potassium maximum	0.5 ppm	0.5 ppm
Silica maximum	1.0 ppm	1.0 ppm
Sodium maximum	0.5 ppm	0.5 ppm
Zinc maximum	0.5 ppm	0.5 ppm

Product Disclaimer Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

NSH-15-05-05-11

Dyno Nobel Inc.

2795 East Cottonwood Parkway, Suite 500, Salt Lake City, Utah 84121 USA
Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com

DYNO
Dyno Nobel

Groundbreaking Performance™