

TITAN[®] 7000i

Gassed Emulsion



Description

TITAN[®] 7000i gassed emulsion has been specifically designed for use in underground mines where mildly¹ reactive ground conditions exist. TITAN 7000i gassed emulsion is a primer sensitive bulk emulsion designed to be pumped from the DynoMiner™ Uphole Loading Truck, which is equipped with a dedicated boom and patented hose retraction unit. TITAN 7000i has excellent water resistance.

Advantages

TITAN 7000i has been specifically formulated to provide excellent up-hole retention in mildly reactive ground. The emulsion has been developed for blasthole diameters of 35-102mm and up to 40 m in length, allowing for a single product for both production and development charging. TITAN 7000i can be gassed to variable densities of 0.8 – 1.25 g/cm³ allowing for tailoring of the product for specific geological conditions.

NOTES:

1. The degree of reactivity is determined by Dyno Nobel standard laboratory reactive ground tests.
2. All Dyno Nobel energy values are calculated using a proprietary Dyno Nobel thermodynamic code – Prodet. Other programs may give different values.
3. The water resistance rating is determined by laboratory methods, and provides an indication of this parameter relative to other products.

Properties

Property	Titan 7000i
Density (g/cm ³)	0.8 – 1.25
Rec. Min. Diam (mm)	35 mm
Energy (MJ/kg) ²	2.93
Water Resistance ³	Excellent
Rec. Sleep Time	See Following Page
RWS ⁴	0.79
RBS (1.05 g/cm ³) ⁴	1.01
RBS (1.15 g/cm ³) ⁴	1.11
RBS (1.25 g/cm ³) ⁴	1.20

Typical Velocities of Detonation

Product	Hole Diameter (mm)	Density (g/cm ³)	Booster	VoD ⁵ (m/s)
TITAN [®] 7000i	102 mm	1.10	400HDP	5300
	45 mm	1.15	150HDP	4500
	38 mm	1.10	150HDP	4000

4. RWS and RBS are relative to ANFO, and determined using a density of 0.82g/cm³ and an energy of 3.7MJ/kg for ANFO.
5. VOD recorded using a continuous VOD method. VODs were measured in PVC pipes at the nominal densities stated.

TITAN 7000i

Gassed Emulsion

Technical
Information



Recommendations

Priming Requirements – TITAN 7000i gassed emulsion is formulated to be booster sensitive. Minimum primer requirements for production and development blasting are a 250g Ringprime® booster and a 32mm x 200mm Powermite® RiGHT cartridge respectively. Smaller booster types may reduce the performance of the explosive. Double priming is recommended if hole dislocation is expected to disrupt the emulsion column.

Shelf Life – TITAN 7000i emulsion matrix has minimum shelf life of three (3) months, when transported and stored under ideal conditions.

Reactive Ground Conditions – TITAN 7000i has been specifically designed for use in mildly reactive (pyritic) ground conditions. For applications in reactive ground conditions please consult your local Dyno Nobel representative to undertake the appropriate test work prior to the development of suitable site specific procedures.

Sleep Time – In **reactive** ground, the sleep time will be dictated by the specific site procedures developed in consultation with the Australian Explosives Industry Safety Group (AEISG) Code of Practice for Elevated Temperatures and Reactive Ground and your local Dyno Nobel representative and regulatory authority. In **non-reactive** ground the maximum sleep time is 30 days.

Ground Temperature – TITAN 7000i is suitable for use in ground with a temperature of 0°C to a maximum of 55°C.

Dangerous Goods Classification

Product Name:	TITAN® 7000i Gassed Series
Correct Shipping Name:	Explosive, Blasting, Type E
UN Number:	0241
DG Class:	1.1D

Safe handling, transportation & storage

First Aid - Detailed first aid information regarding this product is contained on the relevant Dyno Nobel Material Safety Data Sheet.

Safety - All explosives are classified as dangerous goods and can cause personal injury and damage to property if used incorrectly.

Transportation and Storage - All explosives must be handled, transported and stored in accordance with all relevant regulations. Stock should be rotated such that older product is used first.

The information and suggestions contained in this document concern explosive products that should only be dealt with by persons having the appropriate technical skills, training and licence. The results obtained from the use of such products depend to a large degree on the conditions under which the products are stored, transported and used.

While Dyno Nobel makes every effort to ensure the details contained in the document are as accurate as possible, the conditions under which the products are used are not within its control. Each user is responsible for being aware of the details in the document and the product applications in the specific context of the intended use. If technical advice is required in the specific application of the products then you should contact Dyno Nobel for assistance.

Dyno Nobel makes no warranties in relation to the products it sells other than those implied by law. Except to the extent determined by law, Dyno Nobel bears no risk, responsibility or liability arising from the use of the products and the information in this document by the buyer or user of the products.

® TITAN, Ringprime and Powermite are registered trademarks of the Dyno Nobel Group.
™ DynoMiner is a trademark of the Dyno Nobel Group.
© Dyno Nobel Asia Pacific Pty Limited. 2009 Reproduction without permission strictly prohibited.

VERSION NO.: 2.0
Last Updated: 11/09

Dyno Nobel Asia Pacific Pty Limited
282 Paringa Road
Gibson Island, Murarrie QLD 4172
Australia

DYNO
Dyno Nobel

Groundbreaking Performance