

DYNOMINER[®]

BULK EXPLOSIVES DELIVERY EQUIPMENT FOR TODAY'S UNDERGROUND OPERATIONS



DYNO[®]
Dyno Nobel

DYNOMINER Profile as a modular option
Emulsion capacity: 1,270 kg (2,800 lb)
Loading rate: 56 kg/min (125 lbs/min)



DYNOMINER Profile as a removable cassette
Emulsion capacity: 4,500 kg (11,000 lb)
Loading rate: 56 kg/min (125 lbs/min)



DYNOMINER Advance as a removable cassette
Emulsion capacity: 1,800 kg (4,000 lb)
Loading rate: 36 kg/min (80 lbs/min)



DYNOMINER Advance as a modular option
Emulsion capacity: 1,270 kg (2,800 lb)
Loading rate: 36 kg/min (80 lbs/min)

DYNOMINER Profile APS
for long horizontal or vertical downholes
Emulsion capacity: up to 4,400 kg (10,000 lb)
Loading rate: 56 kg/min (125 lbs/min)



DYNOMINER Advance APS
for short horizontal holes
Emulsion capacity: 636 kg (1,400 lb)
Loading rate: 36 kg/min (80 lbs/min)



DYNOMINER Shaft
Emulsion capacity: 1,725 kg (3,800 lb)
Loading rate: 27 to 40 kg/min (60 to 90 lbs/min)

Dyno Nobel can improve your drill and blast efficiency by combining our proven explosives formulations with our reliable and adaptable loading equipment.

DYNOMINER equipment quickly loads large volumes of TITAN® 7000 bulk explosives, at any angle, in a variety of underground construction, quarry and mining applications.

Why Do Our Customers Like DYNOMINER?

- Increased safety
- Easy to operate and maintain
- Reduced manual product handling
- Improved efficiency and flexibility
- Robust design for dependable operation in the underground environment

DYNOMINER Profile

- Units with specialized, high accuracy uphole loading technology for production
- Compatible with most OEM equipment
- Cassette style units are easily removed from chassis
- Gassing option available with DynoLogix™

DYNOMINER Advance

- Units designed for development applications
- Simple, user friendly with remote control operation
- Stand alone air operated unit or hydraulic/electric unit compatible with most OEM carriers
- String loading and gassing options available with DynoLogix™

DYNOMINER Shaft

- Stand alone, air operated units designed for shaft sinking applications
- Manifold with 4 ports that can be operated simultaneously for fast cycle times
- Quietly operates on regulated mine air and has no pumps or moving parts

DYNOMINER®