OIL WELL EXPLOSIVES





#1019

Gelatin Nitroglycerin Dynamite



Product Description

OIL WELL EXPLOSIVES (OWE) have been designed for extreme application of well fracturing and casing recovery of oil and gas wells. The high energy in OWE provides the user with superior performance in well stimulation. OWE will withstand 700 psi (1600 feet of hydrostatic head pressure) for 24 hours with full energy release.

Application Recommendations

- Minimum diameter is 32 mm (1-1/4 in).
- Minimum detonator is No. 8 strength.
- Storage at elevated temperatures and/or high humidity for 12-18 months can reduce the performance of OWE dynamite depending on the diameter. Consult your Dyno Nobel representative for specific recommendations.
- Storage at elevated temperatures and/or high humidity for 1 to 6 months can reduce the performance of Oil Well Explosives depending on the diameter. Consult your Dyno Nobel representative for specific recommendations.
- Dynamites are susceptible to sympathetic detonation when applied in very wet conditions where boreholes are closely spaced and/or where geological conditions promote this effect. Consult your Dyno Nobel representative for recommendations where these conditions exist.
- Care should be exercised in the selection of an initiation system. Consideration should be given to well depth, charge weight and sleep time. Consult your Dyno Nobel representative for recommendations and / or guidance.

Properties

Density	(g/cc) Avg	1.35
Energyª	(cal/g)	1,225
	(cal/cc)	1,655
Relative	1.39	
Relative	2.30	
/elocity c(m/s)		6,400
	(ft/s)	21,000
Detonation Pressure ^c (Kbars)		138
Nater Re	sistance	Excellent

- ^a All Dyno Nobel Inc. energy and gas volume values are calculated using PRODET[™] the computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.
- ^b ANFO = 1.00 @ 0.82 g/cc
- ° Unconfined @ 50 mm (2 in) diameter.



Hazardous Shipping Description

Explosive, Blasting, Type A, 1.1D, UN 0081 II



D-15-08-18-15

Groundbreaking Performance

OIL WELL EXPLOSIVES





Transportation, Storage and Handling

- The user of this product (or any other explosive product) should not leave or abandon undetonated charges in the ground. The leaving or abandoning of undetonated charges constitutes misuse of the product for which Dyno Nobel and its distributors are not responsible.
- OIL WELL EXPLOSIVES must be transported, stored, handled and used in conformity with all applicable federal, state, provincial and local laws and regulations.
- For maximum shelf-life, OIL WELL EXPLOSIVES must be stored in cool, dry and well-ventilated magazines. Dynamite that is stored under warm wet and/or humid conditions can deteriorate quickly, minimizing shelf-life. Dynamite inventory should always be rotated by using the oldest materials first. For recommended good practices in transporting, storing, handling and using this product, see the booklet "Prevention of Accidents in the Use of Explosive Materials" packed inside each case and the Safety Library publications of the Institute of Makers of Explosives.

Diameter	x Length	Quantity per Case	Nominal Case Weight	
mm	in		kg	lbs
50 x 200	2 x 8	34	18.1	39.8

• Oil Well Explosives are available in a wide variety of sizes. Custom sizes are subject to surcharge and may require longer than usual lead times.

Note: All weights are approximate.

• Check with your local Dyno Nobel representative should you have any questions.

Case Dimensions

45 x 34 x 15 cm

17¼ x 13% x 8¼ in

Product Disclaimer Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.



Dyno Nobel Inc. 2795 East Cottonwood Parkway, Suite 500, Salt Lake City, Utah 84121 USA Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com

Groundbreaking Performance