

TECHNICAL DATA SHEET



TROJAN® SPARTAN® SR™

Shock Resistant Cast Booster

Properties

SDS
#1108

Density	g/cc avg	1.65
Velocity	m/sec	7,550
	ft/s	24,800
Detonation Pressure	Kbars	235
Water Resistance	6 months with no loss of sensitivity	
Shelf Life Maximum	5 years from date of production	
Maximum Usage Temperature*	65°C / 150°F	

*Never expose explosive materials to sources of heat exceeding 66°C (150°F) or to open flame, unless such materials or procedures for their use have been recommended for such exposure by the manufacturer.

All Dyno Nobel Inc. energy and gas volume values except Velocity and Detonation Pressure are calculated using PRODET™ the computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.

Velocity and Detonation Pressure are the result of empirical methods during May 2009.

IMPORTANT WARNING !

NEVER USE A DETONATOR LESS THAN 8.89cm (3.5 inch) WITH THE TROJAN SPARTAN SR CAST BOOSTER. MISFIRES MAY RESULT.

Hazardous Shipping Description

- UN 0042 Boosters, 1.1D PG II



PRODUCT DESCRIPTION

TROJAN SPARTAN SR cast boosters are detonator sensitive, high density, high energy molecular explosives available in three sizes designed to optimize initiation of all booster detonator sensitive explosives.

In addition to the internal through-tunnel and detonator well, the TROJAN SPARTAN SR (Shock Resistant) cast booster has an internal sleeve to protect the circuit board in electronic detonators and is designed specifically for use with Dyno Nobel's DigiShot®, DigiShot® Plus, SmartShot®, and DigiShot® Plus 4G electronic detonators. The TROJAN SPARTAN SR can, however, also be used with any detonator (minimum length = 8.89 cm / 3.5 in) that may require additional protection from high shock, water hammer, effects during decking, corner operations or in certain geologies.



The TROJAN SPARTAN SR (Shock Resistant) cast booster also incorporates the unique Caplock™ feature which holds the detonator in place more securely and makes it more difficult for the detonator to be pulled out of capwell position while it is being lowered into the borehole. Even with this new Caplock feature, the detonator can still be removed if necessary.

Product Disclaimer: Please see reverse side.

DYNO®
Dyno Nobel

TECHNICAL DATA SHEET



TROJAN® SPARTAN® SR™

Shock Resistant Cast Booster

Properties Cont.

Packaging

Unit Weight		Unit Dimensions				Case Quantity	Gross Weight/Case	
g	oz	Length		Diameter			kg	lbs
		cm	in	cm	in			
150	5.5	11.9	4.7	3.6	1.4	95	18.9	41.8

Note: All weights and dimensions are approximate.

Case Dimensions

42 x 33 x 14 cm

16 ½ x 13 x 5 ½ in

PRODUCT DESCRIPTION - continued

TROJAN SPARTAN SR cast boosters are formulated from the highest quality PETN and other high explosive materials ensuring reliability, consistency and durability in all blasting environments.

The fluorescent yellow container makes the TROJAN SPARTAN booster more visible on the blast site and reduces the possibility of misplaced charges.

APPLICATION RECOMMENDATIONS

- **NEVER** force the detonator into the through-tunnel, the detonator-well or otherwise attempt to clear these areas if obstructed. If the through-tunnel or detonator-well does not accommodate the detonator, do not use the booster. Notify your Dyno Nobel representative.
- **ALWAYS** use a detonator with a minimum length of 8.89 cm (3.5 in). The detonator well length is 10.2 cm (4.0 in).
- Extremely low temperatures do not affect the performance of cast boosters with commercial detonators. Low temperatures do affect detonators and detonating cord. Be certain your initiation system is suitable for your application in extremely low temperatures. Cast boosters are more susceptible to breakage during handling in extremely cold temperatures.

TRANSPORTATION, STORAGE AND HANDLING

- Dyno Nobel cast boosters must be transported, stored, handled and used in conformity with all federal, state, provincial and local laws and regulations.
- For maximum shelf life (5 years), Dyno Nobel cast boosters must be stored in a cool, dry, well ventilated magazine. Explosive inventory should be rotated. Avoid using new materials before the old.

ADDITIONAL INFORMATION – Visit dynonobel.com for Brochures and Case Studies related to this product.

Product Disclaimer: Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

DYNO
Dyno Nobel