

# TROJAN® SPARTAN®

## Technical Information



## Cast Booster



### Product Description

TROJAN SPARTAN cast boosters are detonator sensitive, high density, high energy molecular explosives available in various sizes designed to optimize initiation of all booster sensitive explosives. All TROJAN SPARTAN boosters are manufactured with an internal through-tunnel and detonator well for easy application with either electric, electronic or nonelectric detonators or 10.6 g/m (50 gr/ft) minimum strength detonating cord.

TROJAN SPARTAN boosters are formulated from the highest quality PETN and other high explosive materials ensuring reliability, consistency and durability in all blasting environments. The fluorescent green container and clear printing makes the TROJAN SPARTAN booster more visible on the blast site (as well as in low light situations) and reduces the possibility of misplaced charges. The redesigned Caplock™ holds the detonator in place more securely and makes it more difficult for the detonator to be pulled out of the capwell position while it is being lowered into the borehole.

### Application Recommendations

- **NEVER** force the detonator into the through-tunnel, the detonator-well or otherwise attempt to clear these areas if obstructed. If the through-tunnel or detonator-well does not accommodate the detonator, do not use the booster. Notify your Dyno Nobel representative.

## Properties

SDS  
#1108

Density (g/cc) Avg	1.65
Velocity (m/sec)	7,550
(ft/s)	24,800
Detonation Pressure (Kbars)	235
Water Resistance	6 months with no loss of sensitivity
Shelf Life Maximum	5 years (from date of production)
Maximum Usage Temperature*	66°C (150°F)

\*Never expose explosive materials to sources of heat exceeding 66°C (150°F) or to open flame, unless such materials or procedures for their use have been recommended for such exposure by the manufacturer.

All Dyno Nobel Inc. energy and gas volume values except Velocity and Detonation Pressure are calculated using PRODET™ the computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.

Velocity and Detonation Pressure are the result of empirical methods during May 2009.

### Hazardous Shipping Description

UN 0042 Boosters, 1.1D PG II



# TROJAN® SPARTAN®

## Technical Information



### Application Recommendations (continued)

- **ALWAYS** use detonating cord with a coreload of 10.6 g/m (50 gr/ft) or higher when initiating the TROJAN SPARTAN booster with detonating cord.
- Minimum detonator is No. 8 strength for temperatures above -40° C (-40° F). A high strength detonator is recommended for temperatures below -40° C (-40° F).
- Extremely low temperatures do not affect the performance of cast boosters with commercial detonators. Low temperatures do affect detonators and detonating cord. Be certain your initiation system is suitable for your application in extremely low temperatures. Cast boosters are more susceptible to breakage during handling in extremely cold temperatures.

### Transportation, Storage and Handling

- Dyno Nobel cast boosters must be transported, stored, handled and used in conformity with all federal, state, provincial and local laws and regulations.
- For maximum shelf life (5 years), Dyno Nobel cast boosters must be stored in a cool, dry, well ventilated magazine. Explosive inventory should be rotated. Avoid using new materials before the old.

### Packaging

Unit Weight		Unit Dimensions				Case Quantity	Gross Weight/ Case	
g	oz	Length		Diameter			kg	lbs
		cm	in	cm	in			
90*	3.2	11.9	4.7	2.7	1.1	150	14.0	30.9
150	5.5	11.9	4.7	3.6	1.4	95	15.0	33.1
200	7	11.7	4.6	4.1	1.6	72	15.6	34.4
350	12	11.9	4.7	5.0	2.0	49	17.6	38.9
400	14	11.9	4.7	5.5	2.2	40	16.8	37.0
450	16	11.9	4.7	5.8	2.3	36	17.4	38.3
900*	32	12.9	5.1	7.9	3.1	18	17.8	39.2

\* The Caplock feature is not available on these boosters because the shells are made of cardboard instead of plastic.

**Note:** All weights and dimensions are approximate.

### Case Dimensions

42 x 33 x 14 cm

16 ½ x 13 x 5 ½ in

**Product Disclaimer** Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

### Dyno Nobel Inc.

2795 East Cottonwood Parkway, Suite 500, Salt Lake City, Utah 84121 USA  
Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com

**DYNO**  
Dyno Nobel

Groundbreaking Performance™