

UREA AMMONIUM NITRATE

Technical
Information



UAN Fertilizer Solution—32%

Product Description

The UREA/AMMONIUM NITRATE (UAN) solution is created by dissolution of the amide and nitrate salt in water. It may have a slight ammonia odor. Approximately 35% UREA blended with 45% AMMONIUM NITRATE makes a fertilizer solution that is 32% nitrogen by weight.

Application Recommendations

The lowest salt-out temperature possible for UAN 32 is 32°F at a ratio of 1.30 AMMONIUM NITRATE to UREA.

UREA is used as a slow release fertilizer. It must be decomposed by microorganisms before it can be assimilated by plants. The AMMONIUM NITRATE is the fast release part of the fertilizer. The plants quickly absorb the nitrate ion and ammonium ion for immediate metabolism.

Consult your local fertilizer dealer for application recommendations

Transportation, Storage and Handling

- The transport of UAN does not require a DOT placard
- UREA/AMMONIUM NITRATE solution will decompose into ammonia, carbon dioxide and nitric acid at 237°F
- **ALWAYS** wash vessels containing UAN thoroughly before attempting repairs requiring welding
- **ALWAYS** restrict it from the drainage Should a large spill of UAN solution occur. The high nitrogen content (32%) will kill foliage if not diluted
- UAN can be handled by the municipal water treatment facility if spilled in a municipality

Properties

SDS
#1138

Total Nitrogen % by weight minimum	32
Urea % by weight typical	40.9 to 31.2
Amine Nitrogen from Urea % by weight	19.1 to 14.5
Ammonium Nitrate % by weight typical	36.9 to 49.9
Nitrate Nitrogen from Ammonium Nitrate % by weight	10.0 to 13.5
% Ammoniacal Nitrogen from Ammonium Nitrate % by weight	2.9 to 3.9
Ammonia % by weight typical	< 0.15 maximum (unbound)
Water % by weight typical	22.1 to 18.8
Ammonium Nitrate to Urea Ratio	0.9 to 1.6
Corrosion inhibitor % by weight typical	0.03 to 0.05
Solution Weight at 60°F (lbs/gal)	~11
Salt-out temperature °F	40° to 32°
Fertilizer Nutrition Designation	32-0-0

Hazardous Shipping Description

- There are no DOT restrictions, other than weight, to transport UAN 32
- Consult MSDS #1138 for more specific and comprehensive information about chemical hazards

Product Disclaimer Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

NCSH-12-11-10-15

Dyno Nobel Inc.

2795 East Cottonwood Parkway, Suite 500, Salt Lake City, Utah 84121 USA
Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com

DYNO
Dyno Nobel

Groundbreaking Performance