

UREA LIQUOR

Technical
Information



70% Aqueous Cattle Feed Supplement

Product Description

UREA LIQUOR solution is created by dissolution of the pure amide directly into clean condensate so there are no ions of any metals present. It is a clear, colorless solution with a slight ammonia odor.

Application Recommendations

UREA LIQUOR is added to cattle feed to boost the protein content. UREA LIQUOR is a nutrient only to animals with rumens that possess the urease enzyme which allows the metabolism of the chemical.

Consult your Dyno Nobel representative for additional information.

Transportation, Storage and Handling

- Hot concentrated UREA LIQUOR solution poses a moderate health hazard to the handler. If tissue is contacted with this hot solution it can cause second degree burns.
- **ALWAYS** wear liquid impervious clothing, gloves and boots. **ALWAYS** protect eyes and face with shield when loading.
- UREA will decompose into ammonia, carbon dioxide and nitric acid at 275°F.
- **ALWAYS** wash vessels containing UREA thoroughly before attempting repairs requiring welding.
- Should a large spill of UREA LIQUOR solution occur, it should be recovered dry.
- **ALWAYS** restrict it from the drainage. The high nitrogen content (46%) may kill foliage if not diluted.
- UREA can be handled by the municipal water treatment facility if spilled in a municipality.
- **NEVER** allow dried UREA solution to come into contact with nitric acid. The resulting chemical is unstable and dangerous.

Properties

SDS
#1136

UREA % by weight	70.0 - 70.5
Water % by weight maximum	29.5 - 30.0
Biuret % by weight maximum	.5
Free Ammonia % by weight	.5
pH	6.5 - 7.5
Salt-out Temperature (open vessel)	135°F – 137°F
Storage Temperature	40 to 80°F
Weight @ 68°F	9.1 lbs/gallon

Hazardous Shipping Description

- The transport of UREA LIQUOR solution is shipped hot in transports that do not have hazard warning placards.
- There are no DOT restrictions, other than weight, to transport UREA solutions. It may have a "HOT" label on the trailer to advise of the elevated temperature of the liquor.
- Consult MSDS #1020 for more specific and comprehensive information about chemical hazards.

Product Disclaimer Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

NCSH-17-05-06-14

Dyno Nobel Inc.

2795 East Cottonwood Parkway, Suite 500, Salt Lake City, Utah 84121 USA
Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com

DYNO
Dyno Nobel

Groundbreaking Performance