

BLASTGEL®

Technical Information



Large Diameter Packaged Booster Sensitive Emulsion



Product Description

BLASTGEL is a large diameter, booster sensitive, water resistant, perchlorate-free packaged emulsion (1000) or emulsion / ANFO blend (1070) explosive specifically formulated to provide cost effective, general blasting performance in open pit, quarry and construction blasting applications. BLASTGEL is packaged in tough, easy-to-handle shot bags that consist of a rugged polyethylene liner surrounded by a woven polypropylene outer package in various diameters.

BLASTGEL is an excellent choice as the complete explosive load in wet holes with a loading density which is ideal for sinking in wet holes. In addition, BLASTGEL, which maintains its consistency when the package is slit, is clean and easy to handle and use as a partial explosive load after which bulk ANFO can be loaded to complete the explosive charge.

Application Recommendations

- **ALWAYS** use a 340 g (12 oz) or larger cast booster at internal product temperatures higher than -18°C (0°F).
- **ALWAYS** use a 454 g (16 oz) or larger cast booster at internal product temperatures below -18°C (0°F). At internal product temperatures below -18°C (0°F), adequate product warm-up time must be allowed after loading into boreholes and before initiation.
- **NEVER** use or store product below -25°C (-13°F)
- **ALWAYS** ensure continuous column loading with all shot bags in contact with either a primer or one another. For column lengths in excess of 9 m (30 ft) or whenever column separation is suspected, multiple priming is recommended.
- **ALWAYS** use a cast primer in contact with each 76 mm and 83 mm diameter bag or

Properties

SDS
#1163

	1000 (US)	1070 (US) ^d	1070 (Can) ^d
Density (g/cc) Avg	1.19 - 1.21	1.23 - 1.25	1.20 - 1.24
Energy^a (cal/g)	650	730	730
(cal/cc)	800	935	915
Relative Weight Strength^{a,b}	0.74	0.83	0.83
Relative Bulk Strength^{a,b}	1.11	1.30	1.27
Velocity^c (m/s)	5,800	5,500	5,500
(ft/s)	19,000	18,000	18,000
Detonation Pressure^c (Kbars)	91	97	95
Water Resistance	Excellent	Excellent	Excellent
Gas Volume^a (moles/kg)	44	44	44
Fume Class	No underground use		
Shelf Life Maximum	1 year (from date of production)		
Maximum Water Depth	45 m (150 ft)	30 m (100 ft)	30 m (100 ft)

^a All Dyno Nobel Inc. energy and gas volume values are calculated using PRODET™ the computer code developed by Dyno Nobel Inc. for its exclusive use. Other computer codes may give different values.

^b ANFO = 1.00 @ 0.82 g/cc

^c Unconfined @ 125 mm (5 in) diameter

^d Product is manufactured at a slightly different density to respond to U.S. and Canadian market needs.

Hazardous Shipping Description

Explosive, Blasting, Type E, 1.5D, UN 0332 II



BLASTGEL®

Technical Information



ensure internal product temperature is higher than 5°C (41°F) to overcome potential lack of adequate charge coupling and ensure reliable bag-to-bag propagation in small diameters. Alternate methods to ensure reliable bag-to-bag coupling may be acceptable. Please consult your Dyno Nobel representative for details.

- The minimum available diameter for BLASTGEL 1000 is 76 mm (3 in) for U.S. applications. The minimum available diameter for BLASTGEL 1070 is 100 mm (4 in) for U.S. applications or 65 mm (2.5 in) for applications in Canada.
- Use with detonating cord is not recommended.
- In wet holes where BLASTGEL is used to build the explosive column above and out of water, once the column is above the water level, **ALWAYS** load one additional cartridge before loading bulk ANFO. Slit the package with a knife near its top before loading to minimize ANFO contact with water.
- Emulsion explosives are susceptible to “dynamic shock” and may detonate at low order or fail completely when applied in very wet conditions, where explosive charges or decks are closely spaced and/or where geological conditions promote this effect. Consult your Dyno Nobel representative for alternate product recommendations when these conditions exist.

Transportation, Storage and Handling

- BLASTGEL must be transported, stored, handled and used in conformity with all applicable federal, state, provincial and local laws and regulations.
- BLASTGEL has a shelf life of one (1) year when stored at temperatures between -18°C and 38°C (0°F and 100°F). Extended storage below -18C can adversely effect performance and reliability of BLASTGEL. Consult your Dyno Nobel representative for more information on extreme cold temperature storage.
- BLASTGEL emulsion explosives with a manufactured date exceeding one (1) year should be inspected prior to use. Consult your local Dyno Nobel representative for guidance. Explosive inventory should be rotated. Avoid using new materials before the old. For recommended good practices in transporting, storing, handling and using this product, see the booklet “Prevention of Accidents in the Use of Explosive Materials” packed inside each case and the Safety Library Publications of the Institute of Makers of Explosives.

Packaging

BLASTGEL is available as follows:

In the U.S.	3.0 in x 10 lb (Blastgel 1000)
	3.5 in x 15 lb (Blastgel 1000)
	4.0 in x 20 lb (Blastgel 1070)
	4.5 in x 25 lb (Blastgel 1070)
	5.0 in x 30 lb (Blastgel 1070)
	5.5 in x 35 lb (Blastgel 1070)
	6.0 in x 40 lb (Blastgel 1070)
	6.5 in x 45 lb (Blastgel 1070)
7.0 in x 50 lb (Blastgel 1070)	
In Canada	65 mm (2.50 in) x 3.1 kg (6.8 lbs)
	76 mm (3.00 in) x 4.0 kg (8.8 lbs)
	83 mm (3.27 in) x 4.5 kg (9.9 lbs)
	95 mm (3.74 in) x 6.0 kg (13.2 lbs)
	115 mm (4.53 in) x 9.2 kg (20.3 lbs)
	125 mm (5.00 in) x 11.3 kg (24.9 lbs)
	138 mm (5.43 in) x 13.6 kg (30.0 lbs)
	152 mm (6.00 in) x 18.0 kg (39.7 lbs)
177 mm (7.00 in) x 22.7 kg (50.0 lbs)	

Note: All weights are approximate

Product Disclaimer Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

Dyno Nobel Inc.

2795 East Cottonwood Parkway, Suite 500, Salt Lake City, Utah 84121 USA
Phone 800-732-7534 Fax 801-328-6452 Web www.dynonobel.com

DYNO
Dyno Nobel

Groundbreaking Performance